

3M™ Overhead Projector

Model 1895

Ultimate Innovation

The ultimate 3M™ Overhead Projector Model 1895 packs a high-resolution, three-element lens for incredible brightness, maximum resolution, and very sharp images. A low-to-high 3,600 and 4,300 lumens effortlessly hurl images across the largest auditoriums. A breakthrough inverted-head design lowers the overall projector height a full 5–1/2 inches, so everyone sees the screen. A color-tuning dial creates edge-to-edge brightness, and a large stage is big enough to fit oversized transparencies. A hush-quiet fan enables listeners to hear every word of your presentation. And, with the flip of a switch, a lamp changer makes replacing lamps a simple job. It also comes with a thermal-protection circuit that disconnects power to lamps in the unlikely event of overheating and a lamp interrupt switch that prevents premature lamp failure when replacing lamps. The fully loaded 3M Overhead Projector Model 1895 is backed by a five-year warranty on all parts and labor.



KEY FEATURES

- > Low-to-high 3,600 to 4,300 lumens output effortlessly hurl images across the largest auditoriums.
- > Breakthrough inverted-head design lowers overall projector height a full 5–1/2 inches, so everyone sees the screen, not the equipment.
- > Large stage fits oversized transparencies.
- > Hush-quiet fan promotes more enjoyable presentations.
- > Thermal-protection circuit disconnects power to lamps in the unlikely event of overheating.
- > Convenient handle and easy-to-use fold-down post for storing and carrying projector
- > Digital clock tracks meeting times
- > Five-year warranty on all parts and labor. Please see product packaging for details of warranty terms.

ORDER NUMBER: X0-0038-0710-4 (former#: 78-9236-6579-4)

OPTIONAL ACCESSORIES: Replacement lamp, roller attachment, roller-attachment film, and dust cover

TECHNICAL SPECIFICATIONS

Specifications subject to change.

OPTICAL PERFORMANCE

- > Head: **Inverted triplet** (three-element) lens
- > Illumination: **4,300 ANSI lumens typical** (3,600 lumens -- low setting)
- > Design: **Transmissive** with folded optical system
- > Stage aperture: **286 mm x 286 mm** (11.25 inches x 11.25 inches)
- > **Color-tuning dial**

LAMP DESCRIPTION

- > **Lamp ejector**
- > **Lamp changer**
- > Lamp Type: **FXL** (82 volts, 410 watts)
- > Lamp Life: **40** hours (high setting), **80** hours (low setting) using Model 1895

PHYSICAL CHARACTERISTICS

- > **Internal high/low switch**
- > Weight: **19.5 lbs.** (8.9 kg)

ELECTRICAL FEATURES

- > **Hush-quiet fan**
- > **Digital clock**
- > Power-cord length: **4.6 m** (15 feet)
- > **Power-cord wrap**

MECHANICAL

- > **Lamp-interrupt switch** shuts off power to lamp when changing to prevent premature failure.
- > **Carrying handle**
- > **Fold-down post**

**Ask
about 3M
LAMPS!**

1.800.328.1371

WWW.3M.COM/meetings

“Wherever there’s a great meeting, you’ll find 3M.”™

Visual Systems Division
Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Canada
P.O. Box 5757
London, Ontario, Canada
N6A 4T1

3M Mexico, S.A. de C.V.
Apartado Postal 14-139
Mexico, D.F. 07070
Mexico

3M Presentation Solutions